

Change Notice No.	Notification date	Implementation date
CN/17/03	10 th January 2017	10 th February 2017

Subject : Change in specifications of Maximum Operating Temperature for mdi AseptiSure TH Hydrophobic PTFE Membrane Cartridge Filters

Scope : This change notification will affect the products with following catalog numbers: (* can be any alphabet or numeral):

- CPTH*****

Background:

In our efforts to update the user regarding product performance related information, the specification of maximum operating temperature for **mdi** AseptiSure TH Hydrophobic PTFE Membrane Cartridge Filters with catalog number as mentioned above has been changed.

Need for Change:

mdi is manufacturing above mentioned products since long time. Based on the validation studies performed, it has been concluded that the above mentioned products can withstand extreme operating temperature up to 95 °C at 2 Kg/cm². Hence, the specification of maximum operating temperature for **mdi** AseptiSure TH Hydrophobic PTFE Membrane Cartridge Filters with catalog number as mentioned above has been changed. No change has been done in any critical dimensions or materials of construction.

The related product literature such as certificate of quality, validation guide, product data sheet, product insert etc will reflect the said changes

How Does It Affect the User:

From a practical point of view this change allows the use of product under more severe conditions of operation. All other product specifications including materials of construction as well as other performance specifications remain unchanged. The accompanying product literature e.g. Certificate of quality, validation guide, product insert etc. will reflect the said change.

- The specifications for maximum operating temperature has been upgraded from 80 °C at < 2 Kg/cm² to 95 °C at < 2 Kg/cm².

Change Notice No.	Notification date	Implementation date
CN/17/03	10 th January 2017	10 th February 2017

Implementation of Change:

mdi AseptiSure TH Hydrophobic PTFE Membrane Cartridge Filters with catalog number as mentioned above, manufactured after the implementation date (**10th February 2017**) will have the said changes. However, the available stock of **mdi** AseptiSure TH Hydrophobic PTFE Membrane Cartridge Filters with old specifications for maximum operating temperature (80 °C at < 2 Kg/cm²) will be received by you till the stocks last.

In case you have any queries, please feel free to contact our Technical Support Team at 'info@mdimembrane.com'.



Head - Quality Assurance
Advanced Microdevices Pvt. Ltd.